
Overview

HP Integrity BL860c i2 Server Blade



- 1. 3 x PCIe Mezzanine Slots
- 2. 24 x DDR3 DIMM Slots

- 3. 2 x SFF SAS HDDs, hot-swap bays
- 4. Two Intel[®] Itanium[®] processor 9300 series sockets

What's New

- Support for HP-UX Virtual Partitions (vPars) v6.0
- Support for HP 300GB 6G SAS 15K SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive
- Support for HP NC553m Dual Port 10Gb FlexFabric Adapter (Ethernet and FCoE)
- Support for HP Smart Array P711m 6G SAS Controller

At A Glance

This document covers the HP Integrity BL860c i2 server blade only. For more information on HP BladeSystem c-Class Enclosures and HP BladeSystem c-Class Interconnect and Mezzanine Components, please see the following:

- HP BladeSystem c3000 Enclosure QuickSpecs: http://h18000.www1.hp.com/products/quickspecs/12790_div/12790_div.html
- HP BladeSystem c7000 Enclosure QuickSpecs: http://h18000.www1.hp.com/products/quickspecs/12810_div/12810_div.html
- HP BladeSystem c-Class Interconnect and Mezzanine Components: http://h18004.www1.hp.com/products/blades/components/c-class-interconnects.html http://h18004.www1.hp.com/products/blades/components/c-class-adapters.html

The HP Integrity BL860c i2 delivers the performance, reliability, and availability on 64-bit operating systems (HP-UX 11i v3, Microsoft Windows® Server 2008 R2 for Itanium-based systems and OpenVMS v8.4) for the ultimate in scalability and flexibility in deployment: To further enrich your cost-efficient, consolidated Integrity blade infrastructure, HP Insight Dynamics - VSE for HP Integrity servers can help with solution components such as HP-UX Virtual Partitions (vPars) v6.0, HP Integrity Virtual Machines, HP Capacity Advisor and Virtualization Manager, HP Global Workload Manager and HP-UX Workload Manager, HP Insight Dynamics - VSE infrastructure orchestration HP Insight Dynamics - VSE Reference Architectures, and HP Serviceguard.



Overview

HP Integrity BL860c i2 server blade includes:

- Processor:
 - Up to two Intel[®] Itanium[®] 9300 Series processors
- Memory:
 - Up to 384 GB of memory. Supporting (24) DDR3 registered memory modules (R-DIMMs)
- Storage Controller:
 - o Embedded HP p410i SAS RAID Controller integrated on system board
 - RAID 1, RAID 0, and HBA mode configuration options
- Internal Drive Support:
 - Supports up to (2) two small form factor (SFF) SAS hot plug hard drives
- Network Controller:
 - Four (4) NIC ports via two (2) embeddedNC532i Dual Port Flex-10 Multifunction Server Adapters NOTE: Flex-10 capability requires OS drivers and the use of an HP Virtual Connect Flex-10 10GbE Ethernet module. Learn more at: www.hp.com/go/virtualconnect NOTE: BL8x0c i2 server blades require Virtual Connect 3.00 or later when used in Virtual Connect configurations NOTE: Each port is autosensing 1Gb/10Gb, and can interoperate with 1Gb HP BladeSystem c-Class interconnect
 - components
 - Plus one (1) additional 10/100 NIC dedicated to Integrity iLO 3 Management
- Mezzanine Support:
 - Three (3) additional I/O expansion slots via mezzanine cards.
 - Supports up to (3) mezzanine cards
 - HP NC553m Dual Port 10Gb FlexFabric Adapter
 - HP NC551m Dual Port 10Gb FlexFabric Adapter
 - HP NC552m 10Gb 2-port Flex-10 Ethernet Adapter
 - HP NC532m Dual Port Flex-10 10GbE BL-c Adapter
 - HP Emulex LPe1205 8Gb FC BL-c HBA (2-Port 8Gb Emulex FC HBA)
 - HP QMH 2562 8Gb FC BL-c HBA (2-Port 8Gb QLogic FC HBA)
 - HP Smart Array P711m/1G FBWC 6G SAS Controller
 - HP Smart Array P700m/512 Controller
 - HP 4X QDR IB CX-2 Dual Port Mezz HCA for HP BladeSystem c-Class
 - HP NC364m 4-Port 1GbE BL-c Adapter
 - HP NC360m 2-Port 1GbE BL-c Adapter
- USB Support:
 - o One (1) internal USB port on the BL860c i2
 - Two (2) External USB ports on the BL860c i2 via SUV cable
- Management:
 - HP Integrity Server Blades Management Software
 - Integrity Integrated Lights-Out 3 (iLO 3) management processor
 - HP Insight Control
 - HP System Management Homepage
 - HP-UX 11i Management Software for Integrity Blades, www.hp.com/go/hpuxblades
 - HP Ignite-UX
 - HP Software Assistant (SWA)
 - HP Dynamic Root Disk (DRD)
 - HP BladeSystem Infrastructure Management Software:
 - HP BladeSystem c-Class Onboard Administrator
 - HP BladeSystem c-Class Virtual Connect
 - Enterprise Management Software
 - Data Protector Software
 - GlancePlus Pak
 - Performance Manager and Agent
- Virtualization with HP Insight Dynamics VSE www.hp.com/go/insightdynamics/integrity
 - o Advanced Infrastructure Management

Overview

- HP Capacity Advisor
- HP Virtualization Manager
- HP Global Workload Manager and HP-UX Workload Manager
- HP Insight Dynamics VSE infrastructure orchestration
- HP Systems Insight Manager
- Partitioning Continuum
 - HP-UX Virtual Partitions (vPars) v6.0
 - HP Integrity Virtual Machines (with HP-UX guest OS's and Windows Guest OS's)
 - HP Process Resource Manager/pSets
 - Secure Resource Partitions
- Continuous availability
 - HP Serviceguard for HP-UX 11i
 - HP Serviceguard Extensions for SAP
 - HP Serviceguard Extensions for Faster Failover
- HP Insight Dynamics VSE Reference Architectures
- Form Factor:
 - HP Integrity BL860c i2 server blade is a full-height, BladeSystem c-Class form factor. The BL860c i2 server blade plugs into the BladeSystem enclosure. In the c7000 enclosure, 8 server blades are supported per 10U enclosure. 4 enclosures can be configured to a standard 42U rack; 32 BL860c i2 server blades can be configured in a fully populated rack. In the c3000 enclosure, 4 BL860c i2 server blades are supported per 6U enclosure.

• Enclosures:

- HP offers two different c-Class server blade enclosures to meet your individual needs:
 - The HP BladeSystem c7000 rack enclosure is 10U high and holds up to 8 HP Integrity BL860c i2 servers plugged vertically. Four (4) enclosures can be configured to a standard 42U rack
 - The HP BladeSystem c3000 rack enclosure is 6U high and holds up to 4 HP Integrity BL860c i2 servers plugged horizontally. Up to 7 enclosures can be configured to a standard 42U rack
 - The HP BladeSystem c3000 Enclosure targets three separate market segments:
 - Remote sites needing between 2 and 8 server blades
 - Mid-sized companies with between 3 and 100 servers in their company
 - Enterprise accounts with special datacenter requirement, such as DC power, or very limited rack power and cooling capacity.
- Server blades, storage blades, and interconnect modules are all designed to fit into the c7000 and c3000 enclosures.
- For additional enclosure information, please see:

http://h18004.www1.hp.com/products/blades/components/enclosures/c-class/index.html.

- Warranty:
 - Protected by HP Services and a worldwide network of HP Authorized Channel Partners. Three-year parts, 3 Year Labor and 3 Year on-site limited global warranty. Certain restrictions and exclusions apply. Hard drives have either a one year or three year warranty; refer to specific hard drive QuickSpecs for details.
- NEBS Compliance:
 - The HP BladeSystem c7000/BL860c i2 configuration offers a NEBS Level 3 DC powered option, which enables equipment operability in network facility environments. NEBS compliance is a requirement for Telecom Carriers and their Equipment Providers that are seeking to install equipment in central offices. They view compliance as key to ensuring personnel safety, protection of property, and operational reliability. There are three distinct certification levels specified in SR-3580, Network Equipment-Building System (NEBS) Criteria Levels. All carrier-grade (CG) products released by HP are evaluated to the NEBS Level 3 criteria, which provides the maximum assurance of equipment operability in network facility environments. The Physical Components are described in GR-63-CORE, while the Electromagnetic Compatibility (EMC) and Safety components are described in GR-1089-CORE.
 - This BL860c i2 system has met NEBS Level 3 and ETSI Certifications: NEBS NRTL Certified to NEBS Level-3 Criteria (GR-63-CORE, GR-1089-CORE) and ETSI Certified to EN 300 019, EN 300 386, and EN 300 753.



Processor One of the following depending on Model	del Intel® Itanium® 9340 (1.6GHz/4-core/20MB/185W); up to 1.73 GHz with Turk Intel® Itanium® 9350 (1.73GHz/4-core/24MB/185W); up to 1.86 GHz with Turk		185W); up to 1.73 GHz with Turbo) Processor
	Dual-Core Processor Intel® Itanium® 9310 (1	1.6GHz/2-core/10MB/	30W) Processor
Upgradeability	Upgradeable to two (2) processors NOTE: The HP Integrity BL860c i2 only supports 1 or 2 processor configurations. Processors must be identical.		
Cache Memory One of the following depending on Model	L2 cache per core; 512KB Instruction, 256KB Data L3 cache; up to 24MB, see processor specifics		
Chipset	Intel Boxboro		
Memory		8 GB (4 x 2 GB D 384 GB (24 x 16 es are DIMM pairs. are is enabled in pairs o ouble Chip Spare is no	f DIMMs. Double Chip Spare requires identical DIMM t supported with 2GB DIMMs; when any number of 2GB
Network Adapter	 Four (4) NIC ports via (2) NC532i Dual Port Flex-1010GbE Multifunction Server Adapter NOTE: Flex-10 capability requires OS drivers and the use of an HP Virtual Connect Flex-10 10GbE Ethernet module. Learn more at: www.hp.com/go/virtualconnect NOTE: BL8xOc i2 server blades require Virtual Connect 3.00 or later NOTE: Each part is autosensing 1Gb/10Gb, and can interoperate with 1Gb HP BladeSystem c-Class interconnect components. One (1) additional 10/100 NIC dedicated to Integrity iLO 3 Management Up to twelve additional Gigabit Ethernet ports via the NC364m Quad-port mezzanine adapter or six additional 10 Gigabit Ethernet ports via the NC552m or the NC532m dual-port mezzanine adapters. 		
Expansion Slots	Three Mezzanine slots, two (2) Type II and one (1) Type I, PCIe x8 Gen2		
Integrated Manageability	Integrity Integrated Lights-Out 3 (iLO 3) Factory installed Integrity iLO 3 Advanced Pack license HP BladeSystem c-Class Onboard Administrator HP BladeSystem c-Class Virtual Connect		
Storage Controller	HP p410i 3Gb SAS2 SAS Channels (one to each HDD)ControllerSupports RAID 1, RAID 0, and HBA mode optionsZero (0) cache, no cache options		RAID 0, and HBA mode options
Maximum Internal Storage	Hot Plug SAS	1.8TB SAS	2 x 900GB SAS



Standard Features

(hp)

Graphics	Integrated ATI RN-50 1280 x 1024 x 16M color (128 MB DDR memory)			
•	Resolution Color Depths Depths 1280 x 1024, 16.7M, 64k, 256,16			
	1024 x 768, 16.7M, 64k, 256, 16			
	800 x 600, 16.7M, 64k, 256, 16			
	640 x 480, 16.7M, 64k, 256, 16			
FlexFabric Support	Dual (2) ports via HP BLc NC553m Dual Port FlexFabric 10Gb Converged Network Adapter Dual (2) ports via HP BLc NC551m Dual Port FlexFabric 10Gb Converged Network Adapter NOTE: BL8x0c i2 server blades require Virtual Connect 3.15 or later NOTE: Each port supports 10GbE Ethernet or 8Gb FCoE traffic.			
	HP NC551m: http://h18004.www1.hp.com/products/quickspecs/13649_div/13649_div.html HP NC553m: http://h18004.www1.hp.com/products/quickspecs/13737_div/13737_div.html			
InfiniBand Support	Optional InfiniBand HCAs are supported by the HP Integrity BL860c i2 Server Blade. The mezzanine circuit board connects directly to the server blade system board.			
	HP 4X QDR InfiniBand ConnectX-2 Dual Port Mezzanine HCA for c-Class BladeSystem (PN 592519- B21)			
	Features:			
	 Negotiates to DDR/QDR speeds Dual ports for redundant path connections 			
	 Dual ports for redundant path connections Support for HP-UX 11i v3 			
	 Supported with HP 4X QDR InfiniBand Switch Module for c-Class BladeSystem (PN 489184- 			
	B21).			
	 For details specifications, please visit: http://www.hp.com/products1/serverconnectivity/adapters/infiniband/specifications.html 			
Fiber Channel Support	Optional Fibre Channel HBAs are supported by the HP Integrity BL860c i2. The mezzanine circuit board connects directly to the server blade system board.			
	8Gb Fibre Channel Host Bus Adapters:			
	QLogic QMH2562 8Gb Fibre Channel Host Bus Adapter for c-Class BladeSystem			
	(PN 451871-B21)			
	 Emulex LPe1205 8Gb Fibre Channel Host Bus Adapter for c-Class BladeSystem (PN 456972-B21) 			
	8Gb Fibre Channel HBAs feature:			
	 8/4/2/1Gb/s auto negotiating speeds 			
	Dual ports for redundant path connections Optimized for UD Compared and expected by third party CAN your days			
	 Optimized for HP Storage and supported by third party SAN vendors Support for HP-UX 11i v3 			
Compatible SAN	HP Integrity BL860c i2 server blades are optimized for HP Storage MSA, EVA, and XP products.			
Smart Array Controller Support	Optional Smart Array Controller is supported by BL860c i2. The mezzanine circuit board connects directly to the server blade system board, and provides connection to off-blade SAS storage via a SAS interconnect switch module in the HP BladeSystem enclosure.			
	 HP Smart Array P711m/1G FBWC 4-ports Ext PCIe x8 6G SAS Controller (PN 513778-B21) Provides support for HP Zoned Storage for BladeSystem Zoned Storage solution requires compatible HP Storage 600 Modular Disk System and HP 			

Standard Features

	 Storage 3Gb SAS BL Switch Supports RAID 6 with Advanced Data Guarding (ADG) Provides support for HP P2000 G3 MSA Support for HP P2000 G3 MSA requires HP Storage 6Gb SAS BL Switch NOTE: For additional details please see: http://www8.hp.com/h20195/v2/GetDocument.aspx?docname=c04111558		
HP USB Options	 External USB DVD drive with 6 ft USB extension cable is supported with c7000 enclosures. The solution includes the following components: External USB DVD drive with 9-inch USB cable Power adaptor, power cable and USB Y-connector 6-foot USB extension cable NOTE: The USB Y-connector goes between the extension cable and the 9-inch USB cable fixed with DVD drive. NOTE: The Y-connector should NOT be placed between the server blade and the 6-foot Extension cable. 		
Integrity Server Blades Management Software and HP Integrity Essentials Software Plug-ins	 HP-UX 11i Management Software for HP Integrity BL860c i2 Server Blade and HP BladeSystem HP Hisight Control for HP-UX 11i HP Pusystem Management HP BladeSystem Integrated Manager in HP System Insight Manager HP BladeSystem -Class Virtual Connect Firmware HP BladeSystem -Class Virtual Connect Firmware HP BladeSystem -Class Virtual Connect Firmware HP BladeSystem Control for HP-UX 11i v3 (Included in Base 0E) Deploy HP Ignite-UX Software Distributor-UX Software Package Builder Dynamic Root Disk (DRD) Monitor HP System Management Homepage Glance Plus Pak Performance Manager and Agent HP Serviceguard Manager Integrity Integrated Lights-Out (iLO) 3 (standard with BL860c i2 servers) Integrity L0 3 Advanced Pack license (included with BL860c i2 servers) Integrity L0 3 Advanced Pack license (included with BL860c i2 servers) Integrity IC 3 advanced Pack license (included with BL860c i2 servers) Integrity Massitile Secture Resource Paritions Data Protector Software Software Assistant (SWA) 		



HP Integrity BL860c i2 Server Blade

Stanuaru Features		
		 HP-UX Workload Manager HP Global Workload Manager Process Resource Manager HP Insight Power Manager HP-UX 11i v3 power management Provision HP Insight Dynamics - VSE infrastructure orchestration Integrate HP Business Technology Optimization IT Management Software HP Insight Dynamics - VSE for HP Integrity server blades Learn More For additional information on HP Integrity server blade management software please visit: http://h18004.www1.hp.com/products/servers/integrity-bl/c-class/860c/compmatrix.html
Glossary of Integrity Server Blades Management Software Product Description	HP BladeSystem Integrated Manager in HP Systems Insight Manager	The HP BladeSystem Integrated Manager is a component in HP Systems Insight Manager (SIM) that provides streamlined management for the entire HP BladeSystem product family. The HP BladeSystem Integrated Manager enables users to quickly navigate their HP blade environments including blade servers, enclosure infrastructures, racks, and integrated switches, via automatically generated blade rack picture views and hierarchical trees. Users are able to conveniently configure, deploy, and manage individual or groups of blade systems. Additionally, users are able to quickly set up logical collections of blade systems for convenient management and control.
	HP Blades Visualization	Used by System Administrators to identify, associate and group blades into collections, using tables, trees, and picture views, and it can also be used to monitor performance and launch Integrity Essentials. NOTE: For more information about Manageability solutions for Integrity Servers go to: http://www.hp.com/go/integrityessentials
	HP GlancePlus Pak	HP GlancePlus Pak provides you with a single product for managing a system's availability and performance. It is an integrated product that includes HP GlancePlus and HP OpenView Performance Agent. As an integrated product, the GlancePlus Pak includes the real-time diagnostic capabilities of GlancePlus and the historical data collection capabilities of the Performance Agent. The performance agent is used with other availability and performance management products, thus providing an integrated real-time and historical performance management solution.
	HP Ignite-UX for HP-UX Deployments	HP Ignite-UX is a free toolset that enables a network install of HP-UX onto multiple PA-RISC and/or Integrity servers on a network. It can also be used to create custom install configurations, or golden images, recover systems remotely, create custom recovery media including tape, CD and DVD, and manage and monitor multiple client installation sessions.
	HP Capacity Advisor	The capacity planning component of HP Insight Dynamics - VSE, HP Capacity Advisor offers the industry's first lightweight, integrated tool for ongoing capacity planning by simulating the placement of application



Standard Features

workloads to help IT administrators improve server utilization. It captures real-world server utilization data to pre-test different scenarios before making changes to critical applications.

- HP VirtualizationThe configuration management component of HP Insight Dynamics VSE,
ManagerManagerHP Virtualization Manager provides a central point of control that allows
you to manage all the resources in your environment, providing a powerful
way to connect IT resources to real business needs. With its easy-to-use
interface you can see all your available virtual and physicals resources and
how they are being used.
- HP Integrity Integrated
Lights-Out (iLO) 3HP Integrity Integrated Lights-Out (iLO) management processors make it
simpler, faster, and less costly to remotely manage your Integrity servers.
HP Integrity iLO 3 ships with a built in Advanced Pack License. iLO Advanced
features enabled in this release: Virtual Media, LDAP directory services, iLO
power measurement, and integration with Insight Power Manager. No
additional iLO licensing is needed.

NOTE: Please see www.hp.com/go/integrityilo for more information

HP OnboardThe Onboard Administrator for the HP BladeSystem enclosure is the brainsAdministratorof the new c-Class infrastructure. Together with the enclosure's HP InsightDisplay, the Onboard Administrator has been designed for both local and
remote administration of HP BladeSystem c-Class. This module and its
firmware provides:

- Wizards for simple, fast setup and configuration
- Highly available and secure access to the HP BladeSystem infrastructure
- Security roles for server, network, and storage administrators
- Automated power and cooling of the HP BladeSystem infrastructure
- Agent-less device health and status
- Thermal Logic power and cooling information and control

NOTE: Please see http://www.hp.com/go/onboardadministrator for more information.

HP Serviceguard Manage	r HP Serviceguard Manager is a graphical user interface (GUI) that provides configuration, administration, and monitoring capabilities for Serviceguard, Serviceguard Extension for RAC, Metrocluster, and Continentalclusters. Using Serviceguard Manager, operators see color-coded icons that provide a big-picture view of multiple clusters. From this big-picture view, operators can drill down and proactively manage clusters, systems (nodes), and packages that run applications.
HP Systems Insight Manager	HP Systems Insight Manager (HP SIM) provides a unified, secure and extensible environment to centrally manage servers, storage and other infrastructure devices across multiple operating system platforms.
HP System Management Homepage	HP System Management Homepage is a web-based interface that consolidates and simplifies the management of individual ProLiant and Integrity servers running Microsoft Windows or Linux operating systems, or HP 9000 and HP Integrity servers running HP-UX 11i. By aggregating data



	from HP Insight Management Agents and other management tools, the System Management Homepage provides a secure and intuitive interface to review in-depth hardware configuration and status data, performance metrics, system thresholds and software version control information. The System Management Homepage can also be used to access the HP Lights- Out Management processor on ProLiant and Integrity servers.
HP Insight Dynamics – VSE for HP Integrity servers	HP Insight Dynamics - VSE is advanced lifecycle management software for HP Integrity servers which allows you to instantly adjust to dynamic business demands - with the new addition of infrastructure orchestration, not only can you easily plan, configure, and automate your physical and virtual resources in the same way, but now you can also provision and modify a complex infrastructure in minutes.
HP-UX Software Assistant (SWA)	HP-UX Software Assistant (SWA) is a command-line based tool that consolidates and simplifies patch management and security bulletin management on HP-UX systems. The SWA tool is new for HP-UX releases as of January 2007, includes Security Patch Check (SPC), and is the HP- recommended utility to use to maintain currency with HP-published security bulletins for HP-UX software.
HP-UX Workload Manager	HP-UX Workload Manager (HP-UX WLM) is a resource management tool that provides automatic CPU resource allocation and application performance management based on your service-level objectives (SLOs) and business priorities. WLM is most effective managing applications that are CPU-bound. It automatically adapts system or partition CPU resources (cores) to the demands, SLOs, and priorities of the running applications. (A core is the actual data processing engine within a processor, where a single processor can have multiple cores, and a core can support multiple execution threads through Hyper-Threading, introduced with HP-UX 11i v3, as discussed below.) It adjusts the CPU allocation of a group of processes known as a workload, basing adjustment on the current needs and performance of the applications in that workload.
HP Global Workload Manager	The workload management capability for HP Integrity servers is provided by the HP Global Workload Manager component of HP Insight Dynamics - VSE. HP Global Workload Manager (gWLM) is an intelligent policy engine that automatically allocates resources among multiple workloads to increase server utilization while meeting service levels for high-priority applications. Designed to work across multiple HP-UX 11i, OpenVMS and Linux environments, the workload management features are ideal for large, centralized IT environments that host applications for many departments.
HP Insight Dynamics infrastructure orchestration	HP Insight Dynamics infrastructure orchestration capabilities let you provision infrastructure in minutes to automatically activate physical and virtual servers, storage, and networking from pools of shared resources. Whether you need a single virtual machine or infrastructure for a complex three-tier application, Insight Dynamics finds available resources, streamlines the approval process, and automatically provisions and configures what's needed across infrastructure silos. Delivering infrastructure to the business becomes faster, more efficient, and more reliable.



Proc Mana	ess Resource ager	 HP Process Resource Manager (HP PRM) is a resource management tool used to control the amount of resources that processes use during peak system load. HP PRM can manage allocation of the following resources: CPU: Ensures a minimum allocation of CPU; can also simultaneously cap CPU resource usage for each group in the configuration. (Starting with HP-UX 11i v3, per-group capping is 	
		 available.) Memory: Ensures a minimum allocation of private real memory; can also cap private memory usage. Allows you to allocate an exact amount of shared memory. Disk bandwidth: Ensures a minimum allocation of disk bandwidth 	
	re Resource itions	One method that HP Insight Dynamics - VSE uses to improve server resource utilization is to consolidate multiple applications within a single operating system image. Secure Resource Partitions combine kernel level security and prove resource management to stack multiple applications within the same operating system. HP Process Resource Manager and HP-UX Workload Manager can dedicate specific resources to specific applications within an operating system image, avoiding resource contention issues. Using HP-UX 11i v3 Security Containment, organizations can ensure that application instances cannot access processes or file from other applications or the system. This ensures that multiple application instances run securely in a consolidated environment, providing the benefits of consolidation while preserving the security of a scale out environment. For software licensing purposes, the maximum number of CPUs in a Secure Resource Partition can be capped.	
Softv	ware Distributor-UX	Software Distributor (SD) is the HP-UX administration tool set used to deliver and maintain HP-UX operating systems and layered software applications. SD is delivered as part of HP-UX; you do not need to download it separately.	
HP-L HP-L	-UX 11i v3 Data Center Operating Environment (DC-OE) -UX 11i v3 Virtual Server Operating Environment (VSE-OE) -UX 11i v3 High Availability Operating Environment (HA-OE) -UX 11i v3 Base Operating Environment (BOE)		
	NOTE: For more complete and up to date information on HP-UX 11i support, please visit the HP-UX11i website at: http://www.hp.com/go/hpux11iblades OpenVMS 8.4 (choice of Mission Critical, Enterprise, or Foundation Operating Environment) NOTE: For more complete and up to date information on OpenVMS support, please visit the OpenVMS website at: www.hp.com/go/openvms		
Oper NOT			
NOT	Microsoft Windows Server 2008 for Itanium-based systems NOTE: For more complete and up to date information on Windows support, please visit the Windows website at: www.hp.com/go/integrity/windows		
Supported Software HP I	nsight Dynamics - VS	E for HP Integrity servers (included within both the VSE-OE and DC-OE),	



Options	which includes the following capabilities for Integrity blades:			
	HP-UX Virtual Partitions (vPars) v6.0 HP Integrity Virtual Machines for HP-UX HP Virtualization Manager HP Capacity Advisor HP-UX Workload Manager or HP Global Workload Manager HP Online Integrity VM Guest Migration HP Secure Resource Partitions HP Serviceguard for HP-UX 11i HP Serviceguard Manager HP Serviceguard Extensions for SAP HP Serviceguard Extensions for Faster Failover HP Insight Control power management			
	GlancePlus Pak Performance Manager and Agent			
Intelligent Manageability	HP Integrity Integrated Lights-Out 3 (iLO 3) Virtual serial console (Multiple, mirrored sessions, with previous context and console log buffer)			
	Virtual Power Button Control LDAP Directory Services iLO 3 power measurement and integration with Insight Power Manager Embedded system health and Integrity fault management Diagnostics and troubleshooting:			
	 virtual front panel log access to Integrity System Event Log Forward Progress Log Blade power consumption reading 			
	Dedicated LAN Connectivity Automatic IP Configuration via DHCP/DNS/WINS browser Command Line and scripted access Industry Standard RC4, 128-bit Secure Sockets Layer (SSL) and Secure Shell (SSH) Security Directory Services Integration (LDAP) Support for 19 user accounts with customizable access privileges NOTE: iLO 3 Advanced Pack license is included with every BL860c i2 server blade. iLO 3 Advanced Pack features enabled in this release are Virtual Media, LDAP Directory Services Integration, iLO power			
Availability	measurement, and integration with Insight power manager. Dual-Port Fibre Channel Mezzanine Card for redundant SAN connection Two hot-plug SAS hard drive bays and integrated RAID (HP Smart Array p410i) controller on every			
	server blade Network adapter teaming (network fault tolerance, transmit load balancing, switch-assisted load balancing) supported on integrated LOMs and with add-in Mezzanine cards. • ECC protected DDR3 memory • Memory double chip spare to overcome two DRAM chip failures • Dynamic Processor resilience and deallocation with HP-UX • Journal file system with HP-UX* • Auto reboot • HP Serviceguard for HP-UX* • HP Serviceguard Extension for RAC for HP-UX* • HP Serviceguard Extension for SAP for HP-UX* • Serviceguard Manager for HP-UX Clusters*			



Standard Features

	 HP Event Monitoring Service HA Monitors for HP-UX HA Toolkits for HP-UX HP Mirrordisk/UX* (Included if purchase HP-UX 11i VSE-OE, HA-OE or DC-OE) Extended Campus Cluster*, HP Metrocluster*, and HP Continentalclusters* for HP UX HP System Insight Manager (SIM) for proactive fault management HP Serviceguard Storage Management Suites for HP-UX* NEBS Level 3 Certified (GR-63-CORE, GR-1089-CORE) NOTE: *Fee based software products.		
Industry Standard Compliance	 ACPI 2.0 Compliant PCIe 2.0 Compliant WOL Support USB 2.0 Support 		
Security	Hardware Security		
	 Administrator's password Integrity iLO 3 access control- 19 customizable local user accounts with assignable rights for power, console, configuration, etc. OA and Integrity iLO 3 Directory Services Integration (LDAP) Integrity iLO 3 access via SSL encryption or SSH Integrity iLO 3 access methods via web, SSH, etc. can be disabled SSL encryption on web console Trusted Platform Module (TPM) option for secure cryptographic key storage, integrates with HP-UX security features 		
	Platform security fundamentals For the past 25 years HP has been building one of the most trustworthy and secure UNIX operating systems on the market. Designed for the optimal protection against both external and internal threats. HP-UX 11i offers industry-leading breadth and depth of UNIX security features. Focused on comprehensive security integration aimed at proactively mitigating risk, reducing compliance cost and accelerating time to implementation, HP-UX security solutions significantly lower IT costs. This set of fully integrated and complementary features is designed to provide layered security with indepth protection of all your enterprise assets by protecting all these aspects of data, systems, data and identity security. HP-UX independently validates its comprehensive security portfolio through Common Criteria security evaluations. For more details, visit: www.hp.com/go/hpux11isecurity		
	Protecting systems:		
	One critical factor in enterprise security is system minimization and hardening. HP-UX 11i offers a set of security features designed to address known and unknown vulnerabilities by running only the services that are needed, thus minimizing a potential point of attack. The following security features have built-in mechanisms not only to minimize and harden the system, but also to detect and react to attack in real time:		
	 Bastille system hardening Host Intrusion Detection System Secure Resource Partitions IPFilter - firewall technology Software Assistant (security bulletin currency) Install-time Security 		

Standard Features

- Boot Authentication
- Standard Mode Security Extensions
- Shadow Passwords
- Strong Random Number Generator

Protecting data:

HP-UX 11i offers data protection in many forms: protecting data in transit, in use and at rest. By using security features designed to protect data in its three forms, HP-UX 11i customers can minimize possible breaches not only in terms of data loss, but in customer trust as well. Several security features offer data protection capabilities to HP-UX customers:

- Encrypted volume and file system
- Trusted Computing Services
- Security containment
- OpenSSL
- IPSec
- Secure Shell
- MD5sum

Protecting Identity:

In modern day global enterprise companies, managing identity is not an easy task, especially as identity management requirements grow to include employees, contractors, partners and suppliers across many countries with various privacy protection laws and regulation. HP-UX 11i dramatically simplifies this critical task by integrating various identity management technologies which offer ease of use and adherence to compliance regulation:

- Identity Management Integration
- Select Access for IdMI
- Role-based Access Control
- AAA Server
- HP Directory Server for HP-UX
- LDAP-UX Client
- Kerberos Server
- Kerberos Client Services
- PAM Kerberos

HP also offers many additional security features available through open source software for HP-UX.

Common Criteria certification

Many enterprise and government customers require this vendor-independent security certification because it increases confidence in the product's security assurance, functionality, quality and effectiveness. Many governments, including the United States, require certification for government IT procurement.

Certification evaluations are only conducted by the evaluation agency after release of the product. HP-UX 11i v3, has been actively evaluated to the Common Criteria (CC) Security standards for many years. A history of our achievements include:

- February 2003: Certification of HP-UX 11i V1 achieves A CC to Evaluation Assurance Level 4
- May 2006: Certification of HP-UX 11i V2 to the current EAL4 Common Criteria



(vPars)
Common Criteria certifications continue to be an integral part of our HP-UX comprehensive security portfolio. HP-UX 11i v3 has successfully completed a new Commercial off the Shelf (COTS) Compartmentalized Operations Protection Profile (CCOPP) evaluation. This new CCOPP evaluation encompasses the extensive range of security solution for HP-UX 11i v3 including soft partitioning or Virtual partitions (vPars) as well as the previously certified hard partitions (nPars).
HP Factory Express offers configuration, customization, integration and deployment services for HP servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed.
Factory Express offers service packages for simple configuration, racking, installation, complex configuration and design services as well as individual factory services, such as image loading, asset tagging, and custom packaging. HP products supported through Factory Express include a wide array of servers and storage: HP Integrity, HP ProLiant, HP Integrity Server Blades, HP ProLiant Server Blades, HP BladeSystem, HP 9000 servers as well as the MSA1xxx, VA7xxx, EVA, XP, rackable tape libraries and configurable network switches.
For more information on Factory Express services for your specific server model please contact your sales representative or go to: http://www.hp.com/go/factory-express .
SCE is a guided self service tool to help sales and non technical people provide customers with initial configurations in 3 to 5 minutes. You may then send the configuration on for configuration help, or use in your existing ordering processes. If you require "custom" rack configuration or configuration for products not available in SCE, please contact HP's Customer Business Center or an Authorized Partner for assistance. http://www.hp.com/products/configurator



Support Services

HP Technology Services for Integrity Servers

HP Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Connect to HP to help prevent problems and solve issues faster. Our support technology lets you to tap into the knowledge of millions of devices and thousands of experts to stay informed and in control, anywhere, any time.

Protect your business beyond warranty with HP Care Pack Services

HP Care Pack Services enable you to order the right service level, length of coverage and response time as you purchase your new server, giving you full entitlement for the term you select.

NOTE: Care Pack Services availability may vary by product and country.

Recommended HP Care Pack Services for optimal satisfaction Integrity Servers:

Optimized Care

HP Proactive Care Advanced - 24x7 coverage, three year Care Pack Service

Achieve a higher return on your product investment with the personal attention from a locally assigned Account Support Manager who delivers recommendations designed to improve availability and performance. Leverage your system's ability to connect to HP for automated problem detection and rapid critical event management to increase stability and reduce unplanned downtime. This recommendation provides 24x7 coverage with four-hour response for hardware and two-hour callback for supported software. Collaborative call management comes with Proactive Care Advanced or you may choose full support from HP where we own all cases through to resolution. HP is a leading provider of support services for most operating systems used on HP BladeSystem with long, successful partnerships with vendors such as Microsoft, Red Hat, VMware, SUSE and others. Purchasing software support from HP simplifies troubleshooting and shortens time to resolution with one call for hardware or software questions.

http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=4AA5-3259ENW&cc=us&lc=en

Basic Care

HP Proactive Care with 24x7 coverage, three year Care Pack Service

HP Proactive Care helps prevent problems and stabilize IT by utilizing secure, real-time, predictive analytics and proactive consultations when your products are connected to HP. This Care Pack Service combines three years' proactive reporting and advice with our 24x7 coverage and enhanced escalation management, four hour hardware response time and two hour call back for software questions on leading industry standard software running on your HP ProLiant server. http://h20195.www2.hp.com/v2/GetPDF.aspx/4AA3-8855ENW.pdf

Related Services

HP Server Hardware Installation

Provides for the basic hardware installation of HP branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner. http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf

Factory Express for Servers and storage

HP Factory Express offers configuration, customization, integration and deployment services for HP servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed. For more information on Factory Express services for your specific server model please contact your sales representative or go to: http://www.hp.com/go/factory-express.

Data Privacy Services

Protect your data through better media management. HP Data privacy services help manage and protect sensitive data to reduce the risk of unauthorized access to private information and help meet compliance requirements. Our retention services



Support Services

allow you to keep drives and other devices upon failure, our removal services provide convenient data sanitization and our recovery services allow you to safely retire IT assets and capture any remaining value from the hardware. www.hp.com/services/dataprivacy

Additional HP Care Pack services can be found at: http://www.hp.com/go/cpc

eSupport

Get connected to HP to improve your support experience

Prevent problems with innovative, automated monitoring tools and proactive services. Combining Proactive Care Services with our remote support technology such as Insight Online provides you with expert advice and personalized, cloud-based automated IT support, helping to prevent unplanned down time and solve problems quickly. For more information, visit: www.hp.com/go/proactiveinsightexperience

HP Support Center

Personalized online support portal with access to information, tools and experts to support HP business products. Submit support cases online, chat with HP experts, access support resources or collaborate with peers. Learn more http://www.hp.com/go/hpsc

HP's Support Center Mobile App** allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime.

HP Insight Remote Support and HP Support Center are available at no additional cost with a HP warranty, HP Care Pack or HP contractual support agreement.

** HP Support Center Mobile App is subject to local availability

Parts and Materials

HP will provide HP-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by HP due to malfunction.



Models

HP Integrity BL860c i2 Base Model

HP Integrity BL860c i2 (2P) AD399A	Processor(s) Supports up to two (2) processors	Two (2) processor sockets; processor modules are configured to order
	Cache Memory	Included with processors
	Memory	Twenty four (24) DIMM sockets; memory DIMMs are configured to order.
	Network Adapter	Four (4) NIC ports via (2) NC532i Dual Port Flex-1010GbE Multifunction Server Adapter NOTE: Flex-10 capability requires OS drivers and the use of an HP Virtual Connect Flex-10 10GbE Ethernet module. Learn more at: www.hp.com/go/virtualconnect NOTE: BL8x0c i2 server blades require Virtual Connect 3.00 or later when used in Virtual Connect configurations NOTE: Each part is autosensing 1Gb/10Gb, and can interoperate with 1Gb HP BladeSystem c-Class interconnect components.
	Storage Controller	One (1) additional 10/100 NIC dedicated to Integrity iLO 3 Management Integrated HP Smart Array p410i SAS Controller
	Hard Drives	Two SFF SAS drive bays; hard disk drives are configured to order
	IO expansion	Three PCIe mezzanine card slots (PCIe Gen2 x8 interface); mezzanine cards are configured to order.
	Optical Drive	None internal to blade server
	Integrity iLO 3	Integrity iLO 3 and Integrity iLO 3 Advance Pack license included.
	Form Factor	Up to 8 supported in HP BladeSystem c7000 Enclosure Up to 4 supported in HP BladeSystem c3000 Enclosure

Configuration Information - Factory Integrated Models

NOTE: This section lists some of the steps required to configure a Factory Integrated Model. To ensure only valid configurations are ordered, HP recommends the use of an HP approved configurator. Contact your local sales representative for information on CTO product offerings and requirements.

NOTE: HP does not allow factory integration of options into standard models listed above.

Configure-to-order servers must start with a CTO Chassis.

NOTE: FIO indicates that this option is a Factory Installable Option.

Step 1: Base Server Blade Configuration

HP Models	HP Integrity BL860c i2 Server Blade NOTE: Adding Option code "#0D1" to the Server Blade PN will integrate the configured blade into the enclosure (which must be on the same order).	AD399A
	Configurable Model ships with:	
	Four embedded 10 GB Ethernet NIC ports with Flex-10 support plus (1) additional 10/100 NIC dedicated to Integrity iLO 3 Management	

Integrated HP Smart Array p410i SAS Controller for internal HDDs Two small form factor (SFF) SAS hot plug hard drive bays

HP Integrity Integrated Lights-Out 3

Step 2: Choose Required Options (one of the following from each list unless otherwise noted):

HP Processors	NOTE: Select minimum one (1) and maximum two (2) processors.				
	Quad-Core Processors				
	HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit	AH386A			
	HP BL8x0c i2 Itanium 9340 (1.6GHz/4-core//20MB/185W) Processor Kit	AH387A			
	HP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor Kit	AH388A			
	Dual-Core Processor				
	HP BL8x0c i2 Itanium 9310 (1.6GHz/2-core/10MB/130W) Processor Kit	AH385A			
HP Memory	NOTE: Select minimum one (1) (2x4GB DIMMs) module or two (2) (2x2GB DIMMs) per server, and maximum of six (6) modules per server (12 modules if 2 processors ordered)				
	HP BL8x0c i2 4GB (2x2GB) PC3-10600 Registered CAS 9 Memory Kit	AM326A			
	HP Integrity BL8x0c i2 8GB (2x4GB) PC3-10600 Registered CAS 9 Memory Kit	AM327A			
	HP Integrity BL8x0c i2 16GB (2x8GB) PC3-10600 Registered CAS 9 Memory Kit	AM328A			
	HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS-9 Memory Kit	AM363A			
	NOTE: Memory Modules consist of pairs of DIMMs.				
	NOTE: DIMMs must be installed in pairs. NOTE: Minimum memory requirement is 8GB.				

Step 3: Choose Additional Options for Factory Integration

HP Hard Drives	NOTE: Hard drives have either a one year or three year warranty; refer to specific
	hard drive QuickSpecs for details.



Configuration Information - Factory Integrated Models

	SAS Hot Plug SFF (2.5-inch) Enterprise (ENT) Drives	
	HP 1.2TB 12G SAS 10K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive	785079-B21
	HP 900GB 12G SAS 10K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive	785075-B21
	HP 600GB 12G SAS 10K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive	785073-B21
	HP 450GB 6G SAS 10K rpm SFF (2.5-inch) Dual Port Enterprise 3yr Warranty Hard Drive	581284-B21
	HP 300GB 12G SAS 15K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive	785099-B21
	HP 450GB 12G SAS 15K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive	785101-B21
	HP 600GB 12G SAS 15K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive	785103-B21
	HP 300GB 12G SAS 10K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive	785071-B21
	HP 146GB 6G SAS 15K rpm SFF (2.5-inch) Dual Port Enterprise 3yr Warranty Hard Drive	512547-B21
	NOTE: Though the disks are 6Gb/12Gb, implementation of the embedded HP SAS RAID controller limits performance of disks.	
	12G SAS Hot Plug Enterprise Performance Solid State Drives	
	HP 200GB 12G SAS Write Intensive SFF 2.5-in 3yr Wty Solid State Drive	802576-B21
	HP 400GB 12G SAS Write Intensive SFF 2.5-in 3yr Wty Solid State Drive	802580-B21
	HP 800GB 12G SAS Write Intensive SFF 2.5-in 3yr Wty Solid State Drive	802584-B21
HP Ethernet Mezzanine Options	HP NC364m Quad Port 1GbE BL-c Adapter	447883-B21
options	NOTE: Provides four additional Gigabit Ethernet ports per I/O expansion slot. NOTE: BL860c i2 supports HP Virtual Connect Ethernet Interconnect Modules. See: http://www.hp.com/go/bladesystem/virtualconnect for complete details.	
	HP NC360m Dual Port 1GbE BL-c Adapter NOTE: Provides two additional Gigabit Ethernet ports per I/O expansion slot.	445978-B21
	HP NC552m 10Gb 2-port Flex-10 Ethernet Adapter NOTE: Provides Flex-10 connectivity when used in conjunction with the HP Virtual Connect Flex-10 10Gb Ethernet Module for the c-Class BladeSystem Option (P/N 455880-B21).	610609-B21
	HP NC532m Dual Port 10GbE Multifunction BL-c Adapter NOTE: Provides Flex-10 connectivity when used in conjunction with the HP Virtual Connect Flex-10 10Gb Ethernet Module for the c-Class BladeSystem Option (P/N 455880-B21).	467799-B21
HP FlexFabric Mezzanine Options	HP NC553m 10Gb 2-port FlexFabric Adapter NOTE: Provides Ethernet and FCoE connectivity when used in conjunction with HP Virtual Connect FlexFabric 10Gb/24-Port Module (PN 571956-B21).	613431-B21
	NOTE: Please see the QuickSpecs for Technical Specifications and additional information: HP NC551m:	
	http://h18004.www1.hp.com/products/quickspecs/13649_div/13649_div.html HP NC553m: http://h18004.www1.hp.com/products/quickspecs/13737_div/13737_div.html	
	HP Virtual Connect FlexFabric Module http://h18004.www1.hp.com/products/quickspecs/13652_div/13652_div.html	
HP Fibre Channel	QLogic QMH2562 8Gb Fibre Channel Host Bus Adapter for c-Class BladeSystem	451871-B21
Mezzanine Options	Emulex LPe1205 8Gb Fibre Channel Host Bus Adapter for c-Class BladeSystem NOTE: BL860c i2 supports HP Virtual Connect Fibre Channel Interconnect Modules.	456972-B21



Configuration Information - Factory Integrated Models

See: http://www.hp.com/go/bladesystem/virtualconnect for complete details.

HP Infiniband Mezzanine Options	HP 4X QDR InfiniBand ConnectX-2 Dual Port Mezzanine HCA for c-Class BladeSystem NOTE: Provides DDR/QDR InfiniBand connectivity when used in conjunction with HP BLc 4X QDR IB Switch for HP BladeSystem c-Class (PN 489184-B21). NOTE: For more support details, please visit the following web-page: http://www.hp.com/products1/serverconnectivity/adapters/infiniband/ specifications.html	592519-B21
HP Security - TPM	HP Integrity BL8x0c i2 Trusted Platform Module NOTE: The TPM must be installed by the factory.	AM331A

Step 4: Choose Additional Options for Field Upgrades

NOTE: For additional options, please refer to the "Core Options" and "Additional Options" section below. For additional options, including server blade enclosures interconnect, mezzanine options and power subsystem options; please see the Core Options and Additional sections below; or the following:

HP BladeSystem c-Class Enclosures QuickSpecs: -HP BladeSystem c3000 Enclosure QuickSpecs: http://h18000.www1.hp.com/products/quickspecs/12790_div/12790_div.html -HP BladeSystem c7000 Enclosure QuickSpecs: http://h18000.www1.hp.com/products/quickspecs/12810_div/12810_div.html -and HP BladeSystem c-Class Interconnect and Mezzanine Components: http://h18004.www1.hp.com/products/blades/components/c-class-interconnects.html http://h18004.www1.hp.com/products/blades/components/c-class-adapters.html



Core Options

HP Ethernet Mezzanine Options	HP NC364m Quad Port 1GbE BL-c Adapter NOTE: Provides four additional Gigabit Ethernet ports per each I/O expansion slot.	447883-B21
	HP NC360m Dual Port 1GbE BL-c Adapter NOTE: Provides two additional Gigabit Ethernet ports per each I/O expansion slot.	445978-B21
	HP NC552m 10Gb 2-port Flex-10 Ethernet Adapter NOTE: Provides Flex-10 connectivity when used in conjunction with the HP Virtual Connect Flex-10 10Gb Ethernet Module for the c-Class BladeSystem Option (P/N 455880-B21).	610609-B21
	HP NC532m Dual Port 10GbE Multifunction BL-c Adapter	467799-B21
	NOTE: Provides Flex-10 connectivity when used in conjunction with the Provides Flex-10 connectivity when used in conjunction with the HP Virtual Connect Flex-10 10Gb Ethernet Module for the c-Class BladeSystem Option (P/N 455880-B21).	
HP FlexFabric Mezzanine Options	HP NC553m 10Gb 2-port FlexFabric Adapter NOTE: Provides Ethernet and FCoE connectivity when used in conjunction with HP Virtual Connect FlexFabric 10Gb/24-Port Module (PN 571956-B21).	613431-B21
	NOTE: Please see the QuickSpecs for Technical Specifications and additional information: HP NC551m:	
	http://h18004.www1.hp.com/products/quickspecs/13649_div/13649_div.html HP NC553m:	
	http://h18004.www1.hp.com/products/quickspecs/13737_div/13737_div.html HP Virtual Connect FlexFabric Module	
	http://h18004.www1.hp.com/products/quickspecs/13652_div/13652_div.html	
HP Fiber Channel	Emulex LPe1205 8Gb Fibre Channel Host Bus Adapter for c-Class BladeSystem	456972-B21
Mezzanine Options	OLARIA OMULTER OCH Filme Champel Unet Due Adapter for a Class Diade System	
	QLogic QMH2562 8Gb Fibre Channel Host Bus Adapter for c-Class BladeSystem	451871-B21
HP Processors	Quad-Core Processors	451871-B21
		451871-B21
	Quad-Core Processors	
	Quad-Core Processors HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit	АН386А
	Quad-Core Processors HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit HP BL8x0c i2 Itanium 9340 (1.6GHz/4-core//20MB/185W) Processor Kit	AH386A AH387A
	Quad-Core Processors HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit HP BL8x0c i2 Itanium 9340 (1.6GHz/4-core//20MB/185W) Processor Kit HP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor Kit	AH386A AH387A
	Quad-Core Processors HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit HP BL8x0c i2 Itanium 9340 (1.6GHz/4-core//20MB/185W) Processor Kit HP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor Kit Dual-Core Processor	AH386A AH387A AH388A
	Quad-Core Processors HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit HP BL8x0c i2 Itanium 9340 (1.6GHz/4-core//20MB/185W) Processor Kit HP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor Kit Dual-Core Processor HP BL8x0c i2 Itanium 9310 (1.6GHz/2-core/10MB/130W) Processor Kit NOTE: HP Integrity BL860c i2 processor upgrade kits contain one processor. Processors in a given server blade must be identical. No mixing of processor models	AH386A AH387A AH388A
	Quad-Core Processors HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit HP BL8x0c i2 Itanium 9340 (1.6GHz/4-core//20MB/185W) Processor Kit HP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor Kit Dual-Core Processor HP BL8x0c i2 Itanium 9310 (1.6GHz/2-core/10MB/130W) Processor Kit NOTE: HP Integrity BL860c i2 processor upgrade kits contain one processor. Processors in a given server blade must be identical. No mixing of processor models is allowed.	AH386A AH387A AH388A
HP Processors	Quad-Core Processors HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit HP BL8x0c i2 Itanium 9340 (1.6GHz/4-core//20MB/185W) Processor Kit HP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor Kit Dual-Core Processor HP BL8x0c i2 Itanium 9310 (1.6GHz/2-core/10MB/130W) Processor Kit NOTE: HP Integrity BL860c i2 processor upgrade kits contain one processor. Processors in a given server blade must be identical. No mixing of processor models is allowed. NOTE: The Integrity BL860c i2 only supports 1 or 2 processor configurations.	АН386А АН387А АН388А АН385А
HP Processors	Quad-Core ProcessorsHP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor KitHP BL8x0c i2 Itanium 9340 (1.6GHz/4-core//20MB/185W) Processor KitHP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor KitDual-Core ProcessorHP BL8x0c i2 Itanium 9310 (1.6GHz/2-core/10MB/130W) Processor KitNOTE: HP Integrity BL860c i2 processor upgrade kits contain one processor.Processors in a given server blade must be identical. No mixing of processor models is allowed.NOTE: The Integrity BL860c i2 only supports 1 or 2 processor configurations.HP BL8x0c i2 4GB (2x2GB) PC3-10600 Registered CAS 9 Memory Kit	AH386A AH387A AH388A AH385A AH385A
HP Processors	Quad-Core ProcessorsHP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor KitHP BL8x0c i2 Itanium 9340 (1.6GHz/4-core//20MB/185W) Processor KitHP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor KitDual-Core ProcessorHP BL8x0c i2 Itanium 9310 (1.6GHz/2-core/10MB/130W) Processor KitNOTE: HP Integrity BL860c i2 processor upgrade kits contain one processor.Processors in a given server blade must be identical. No mixing of processor models is allowed.NOTE: The Integrity BL860c i2 only supports 1 or 2 processor configurations.HP BL8x0c i2 4GB (2x2GB) PC3-10600 Registered CAS 9 Memory KitHP Integrity BL8x0c i2 8GB (2x4GB) PC3-10600 Registered CAS 9 Memory Kit	AH386A AH387A AH388A AH385A AH385A AM327A
HP Processors	Quad-Core Processors HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit HP BL8x0c i2 Itanium 9340 (1.6GHz/4-core/20MB/185W) Processor Kit HP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor Kit Dual-Core Processor HP BL8x0c i2 Itanium 9310 (1.6GHz/2-core/10MB/130W) Processor Kit NOTE: HP Integrity BL860c i2 processor upgrade kits contain one processor. Processors in a given server blade must be identical. No mixing of processor models is allowed. NOTE: The Integrity BL860c i2 only supports 1 or 2 processor configurations. HP BL8x0c i2 4GB (2x2GB) PC3-10600 Registered CAS 9 Memory Kit HP Integrity BL8x0c i2 8GB (2x4GB) PC3-10600 Registered CAS 9 Memory Kit HP Integrity BL8x0c i2 16GB (2x8GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HO HE HE MEMORY Modules consist of pairs of DIMMS.	AH386A AH387A AH388A AH385A AH385A AM326A AM327A AM328A
HP Processors	Quad-Core Processors HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit HP BL8x0c i2 Itanium 9340 (1.6GHz/4-core//20MB/185W) Processor Kit HP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor Kit Dual-Core Processor HP BL8x0c i2 Itanium 9310 (1.6GHz/2-core/10MB/130W) Processor Kit NOTE: HP Integrity BL860c i2 processor upgrade kits contain one processor. Processors in a given server blade must be identical. No mixing of processor models is allowed. NOTE: The Integrity BL860c i2 only supports 1 or 2 processor configurations. HP BL8x0c i2 4GB (2x2GB) PC3-10600 Registered CAS 9 Memory Kit HP Integrity BL8x0c i2 16GB (2x8GB) PC3-10600 Registered CAS 9 Memory Kit HP Integrity BL8x0c i2 16GB (2x8GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 16GB (2x8GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS-9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS-9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS-9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS-9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS-9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered C	AH386A AH387A AH388A AH385A AH385A AM326A AM327A AM328A
HP Processors	Quad-Core Processors HP BL8x0c i2 Itanium 9320 (1.33GHz/4-core/16MB/155W) Processor Kit HP BL8x0c i2 Itanium 9340 (1.6GHz/4-core/20MB/185W) Processor Kit HP BL8x0c i2 Itanium 9350 (1.73GHz/4-core/24MB/185W) Processor Kit Dual-Core Processor HP BL8x0c i2 Itanium 9310 (1.6GHz/2-core/10MB/130W) Processor Kit NOTE: HP Integrity BL860c i2 processor upgrade kits contain one processor. Processors in a given server blade must be identical. No mixing of processor models is allowed. NOTE: The Integrity BL860c i2 only supports 1 or 2 processor configurations. HP BL8x0c i2 4GB (2x2GB) PC3-10600 Registered CAS 9 Memory Kit HP Integrity BL8x0c i2 8GB (2x4GB) PC3-10600 Registered CAS 9 Memory Kit HP Integrity BL8x0c i2 16GB (2x8GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS 9 Memory Kit HO HE HE MEMORY Modules consist of pairs of DIMMS.	AH386A AH387A AH388A AH385A AH385A AM326A AM327A AM328A



Core Options

HP Hard Drives NOTE: Hard drives have either a one year or three year warranty; refer to specific hard drive QuickSpecs for details. SAS Hot Plug SFF (2.5-inch) Enterprise (ENT) Drives HP 1.2TB 12G SAS 10K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive 785079-B21 HP 900GB 12G SAS 10K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive 785075-B21 785073-B21 HP 600GB 12G SAS 10K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive HP 450GB 6G SAS 10K rpm SFF (2.5-inch) Dual Port Enterprise 3yr Warranty Hard 581284-B21 Drive HP 300GB 12G SAS 15K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive 785099-B21 HP 450GB 12G SAS 15K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive 785101-B21 HP 600GB 12G SAS 15K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive 785103-B21 HP 300GB 12G SAS 10K rpm SFF (2.5-inch) Enterprise 3yr Warranty Hard Drive 785071-B21 HP 146GB 6G SAS 15K rpm SFF (2.5-inch) Dual Port Enterprise 3yr Warranty Hard 512547-B21 Drive NOTE: Though the disks are 6Gb/12Gb, implementation of the embedded HP SAS RAID controller limits performance of disks NOTE: Please see the QuickSpecs for Technical Specifications and additional information related to HDDs: http://h18000.www1.hp.com/products/quickspecs/12244_div/12244_div.html (Worldwide) **12G SAS Hot Plug Enterprise Performance Solid State Drives** HP 200GB 12G SAS Write Intensive SFF 2.5-in 3yr Wty Solid State Drive 802576-B21 HP 400GB 12G SAS Write Intensive SFF 2.5-in 3yr Wty Solid State Drive 802580-B21 HP 800GB 12G SAS Write Intensive SFF 2.5-in 3yr Wty Solid State Drive 802584-B21

> **NOTE:** Please see the QuickSpecs for Technical Specifications and additional information related to HDDs: http://h18000.www1.hp.com/products/quickspecs/14038_div/14038_div.html

(Worldwide)



Additional Options

HP Smart Array Controller	HP Smart Array P711m/1G 6Gb FBWC 4-ports Ext Mezzanine SAS Controller NOTE: The P711M will function as a SAS RAID controller when connected to MDS600 disk subsystem via the HP BLc 6Gb SAS Switch. In the RAID mode, HP-UX 11i v3 is supported.	513778-B21
	NOTE: The P711mM will function as a Pass-Thru when connected to the HP P2000G3 SAS Storage Array via the HP BLc 6Gb SAS Switch. In the Pass-Thru mode, HP-UX 11i v3 is supported. For more details please see QuickSpec:	
	http://h18004.www1.hp.com/products/quickspecs/14035_div/14035_div.html	
	Optional Upgrade	
	HP Smart Array P-Series Low Profile Battery	452348-B21
	NOTE: The P700M will function as a SAS RAID controller when connected to MDS600 disk subsystem via the Storage 3Gb SAS Switch. In the RAID mode, HP-UX 11i v3 and Integrity for Windows 6.2 are supported. NOTE: The P700M will function as a Pass-Thru when connected to the MSA2300sa G2 SAS Storage Array via the Storage 3Gb SAS Switch. In the Pass-Thru mode, HP-UX 11i v3 and Integrity for Windows 6.2 are supported.	
	NOTE: The optional battery is required for Advanced Data Guarding (enabled with SSAP), RAID 6, and is highly recommended for RAID 5 implementations NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/13175_div/13175_div.html	
HP Infiniband Mezzanine Options	HP 4X QDR InfiniBand ConnectX-2 Dual Port Mezzanine HCA for c-Class BladeSystem NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/12586_div/12586_div.html	592519-B21
HP Ethernet Interconnects	HP Virtual Connect FlexFabric 10Gb/24-port Module for c-Class BladeSystem NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/13652_div/13652_div.html	571956-B21
HP Storage Blades	HP D2200sb PCIe Storage Blade	AP880A
nr Stolage Blaues	NOTE: Please see QuickSpecs for Technical Specifications and additional options at: http://h18004.www1.hp.com/products/quickspecs/13714_div/13714_div.html	APOOUA
HP USB Options	HP Integrity USB External DVD/RW Drive	AT120B
	 NOTE: The HP Integrity USB External DVD-RW drive solution includes the External DVD drive (AT120B) with 9 inch USB cable, power adaptor, power cable and Y-connector and 6-foot USB extension cable. NOTE: The USB Y-connector goes between the extension cable and the 9-inch USB cable fixed with DVD drive. NOTE: The Y-connector should NOT be placed between the server blade and the 6-foot Extension cable. 	
HP Care Pack Services	HP offers a range of support services and additional services. For a complete listing of services, see: HP.com external site: http://www.hp.com/services/bladesystemservices	
	HP Critical Service	



HP Integrity BL860c i2 Server Blade

Additional Options

HP CP 1Y Critical Service	HA112A1
HP CP 3Y Critical Service	HA112A3
Installation Services	
HP CP Installation	HA113A1
NOTE: For more information: http://www.hp.com/services/bladesystemservices	



Memory

DIMM installation guidelines:

- 1. All DIMMs must be DDR3 registered memory modules (R-DIMMs)
- 2. Both DIMM slots in a memory bank must be populated. A memory bank in this case is identical with a memory pair. A PCU will drive banks A through F.
- 3. Banks must be populated in sequential Alphabetic order, starting with bank A for CPUO, followed by bank A for CPU1, etc.
- 4. Both DIMMs in a memory bank must be identical.
- 5. DIMMs must be installed in decreasing capacity with the largest DIMMs installed in the smallest numbered DIMM slot.

HP Integrity BL860c i2 Server Blade

Standard Memory

8 GB Registered PC3-10600 DDR3 1333MHz ECC DIMMs (2 x 4 GB) Memory Bus Bandwidth: 4.8GT/s

Standard Memory Plus Optional Memory

Up to 384GB of DDR3 registered memory is available.

Following are memory options available from HP:

HP MemoryHP BL8x0c i2 4GB (2x2GB) PC3-10600 Registered CAS 9 Memory KitAM326AHP Integrity BL8x0c i2 8GB (2x4GB) PC3-10600 Registered CAS 9 Memory KitAM327AHP Integrity BL8x0c i2 16GB (2x8GB) PC3-10600 Registered CAS 9 Memory KitAM328AHP BL8x0c i2 32GB (2x16GB) PC3-10600 Registered CAS-9 Memory KitAM363ANOTE: Must be installed in pairs.NOTE: DIMMs must be installed in decreasing capacity with the largest DIMMs smallest numbered slot.



Storage



1 2 x SFF SAS Hot Plug Hard Drives

Hard Drives

SAS Hot Plug SFF Enterprise (ENT) Drives

NOTE: Hard drives have either a one year or three year warranty; refer to specific hard drive QuickSpecs for details.

	Quantity Supported	Position Supported	Controller
	2	1-2	HP Smart Array P410i Controller
1.2TB 12G 10K SFF			
900GB 12G 10K SFF			
600GB 12G 10K SFF			
450GB 6G 10K SFF			
300GB 12G 10K SFF			
300GB 12G 15K SFF			
450GB 12G 15K SFF			
600GB 12G 15K SFF			
146GB 6G 15K SFF			

6G SAS Hot Plug Enterprise Performance Solid State Drives

NOTE: Hard drives have either a one year or three year warranty; refer to specific hard drive QuickSpecs for details.

	Quantity Supported	Position Supported	Controller
200GB/400GB/800GB 6G SLC SFF	2	1-2	HP Smart Array P410i Controller





Power Specifications

NOTE: The HP Power Advisor is a tool provided by Hewlett-Packard to assist in the estimation of power consumption and proper selection of components including power supplies at a system, rack, and multi-rack level. A variety of additional features are also provided including a condensed bill of materials, a cost of owner ship calculator, and a power report. For additional information please visit: HP Power Advisor: http://h18004.www1.hp.com/products/solutions/power/index.html



Technical Specifications

System Unit	Dimensions	Height	14.42 in (36.63 cm)	
		Depth	20.02 in (50.85 cm)	
		Width	2.03 in (5.16 cm)	
	Shipping Dimensions	Height	21.50 in (54.61 cm)	
		Depth	26.0- in (66.04 cm)	
		Width	10.00 in (25.4 cm)	
	Weight	Maximum	26.5 lbs (12.02 kg)	
	Temperature Range*	Operating	10° to 35° C (50° to 95° F)	
		Non-Operating	-40° to 60° C (-40° to 140° F)	
		Storage	-20° to 60° C (-4° to 140° F)	
		Maximum Wet Bulb Temperature	30° C (86° F)	
	Relative Humidity**	Operating	15% to 80%	
	-	Shipping	10% to 90%	
		Storage	10% to 90%	
	3,048m (10,000 ft) or 70 K KPa/4.4 psia. ** Storage maximum humi	pa/10.1 psia. Upper non-op	sunlight allowed. Upper operating limit is berating limit is 9,144 m (30,000 ft) or 30.3 aximum temperature of 45°C (113°F). Altitude mum of 70 KPa.	
Embedded SAS RAID HP Smart Array p410i	Disk Drive and Enclosure Interface	3Gb SAS (Serial Attached SCSI)		
Controller	SAS Connectors	2 internal (SFF8484) x4 v	vide part connectors	
	Cache Memory Speed	DDR2-800 memory provi	ides up to 4.2 GB/s maximum bandwidth	
	Server Interface	X1 5.0Gbps PCIe provides	s 1GB/s maximum bandwidth.	
	SAS Speed	Two x1 3G SAS provide 6	00MB/s maximum bandwidth.	
	Cache Memory	Not supported.		
	Logical Drives Supported	Up to 2 logical volumes		
	Maximum Logical Drive Capacity	Up to 64 logical		
	Host Memory Addressing	64-bit, supporting greate	er than 4GB server memory space	
	RAID Support	RAID 0 (Striping), RAID 1 (mirroring), and1+0 (Mirrored and Striped) (not supported with BL8x0c i2 blades)		
	Upgradeable Firmware	 Upgradeable Firmware with Recovery ROM features Online Drive Flash requires 256MB, 512MB, or 1GB cache mod 		
Embedded Dual NC532i	Network Interface	1000Base-Sx		
10 Gigabit NICs	Compatibility	IEEE 802.ip QoS 802.3x flow control, and 802.3ap 10GBase-KR		
	Data Transfer Method	PCI Express, four lanes (x4)		
	Network Transfer Rate (Theoretical Maximum Values)	1Dual 10Gb parts offer up to 40Gb/s bidirectional theoretical through		
Environment-friendly Products and Approach	End-of-life Management and Recycling	nt Hewlett-Packard offers end-of-life HP product return, trade-in, and recycling programs in many geographic areas. For trade-in information		



Technical Specifications

please go to: http://www.hp.com/go/green. To recycle your product, please go to: http://www.hp.com/go/green or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/green. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.



Summary of Changes

Date	Version History	Action	Description of Change:
		Information updated in storage section.	
		Added	Skus added in Configuration Information - Factory Integrated
			Models and Core options
			• 802576-B21
			• 802580-B21
			• 802584-B21
		Removed	Skus removed in Configuration Information - Factory
			Integrated Models and core options
			• 632492-B21
			• 632494-B21
30-Mar-2015	From Version 20 to 21	Changed	Configuration Information - Factory integrated models and
		5	Storage sections were updated
		Added	Skus Added:
			• 785079-B21
			• 785075-B21
			• 785073-B21
			• 785099-B21
			• 785101-B21
			• 785103-B21
			• 785071-B21
		Removed	Skus deleted:
			• 718160-B21
			• 619291-B21
			• 581286-B21
			• 627117-B21
			• 507127-B21
01-Dec-2014	From Version 19 to 20	Changed	Standard Features, Configuration Information - Factory
		changea	Integrated Models, Core Options and Memory sections were
			updated
		Added	Technology Services for Integrity Servers and Protect your
			business beyond warranty with HP Care Pack Services
			sections were added to Support Services
		Removed	Obsolete skus deleted:
			• 507125-B21
			• 512545-B21
			• 580151-B21
			• 508226-B21
			• 411243-B21
			• BS580A
			• AQ697A
18-Apr-2014	From Version 18 to 19	Changed	Service and Support and Basic Care were revised.
10-Dec-2013	From Version 17 to 18	Added	HP 1.2TB 6G SAS 10K rpm SFF Dual Port Enterprise 3yr
			Warranty Hard Drive was added to Hard Drives.
24-Sep-2012	From Version 16 to 17	Changed	Changes made in Standard Features section.
07-May-2012	From Version 15 to 16	Changed	Memory was revised throughout.
10-Feb-2012	From Version 14 to 15	Changed	Changes made to the USB Options sections. And the Support
			Services section was added.
14-Nov-2011	From Version 13 to 14	Changed	FlexFabric Support, Smart Array Controller Support,
		_	Supported Software Options, HP FlexFabric Mezzanine
			Options and Hard Drives were revised.



Summary of Changes

30-Sep-2011	From Version 12 to 13	Changed	Changes made within the Overview, Standard Features, Configuration Information and Options sections.
02-Aug-2011	From Version 11 to 12	Changed	Hard Drives Descriptions changes made.
20-Jun-2011	From Version 10 to 11	Changed	6G SAS Hot Plug Enterprise Performance Solid State Drives were added to Hard Drives
			HP Ultrium Tape Drives were removed from Additional Options
09-May-2011	From Version 9 to 10	Changed	Processor descriptions were revised
			Maximum internal storage was increased to 1.8TB
			HP 900GB 6G SAS 10K rpm SFF Enterprise Drive was added to Hard Drives
15-Apr-2011	From Version 8 to 9	Added	FlexFabric Support and InfiniBand Support were added to Standard Features
			HP BLc NC551m Dual Port FlexFabric 10Gb Converged Network Adapter was added to HP Ethernet Mezzanine Options
			HP c-Class Mezzanine Options was added to Step 3
			HP Ethernet Interconnects was added to Additional Options
18-Mar-2011	From Version 7 to 8	Changed	Processors, Memory and Hard Drive product descriptions were revised
			HP USB Options was added to Standard Features and Additional Options
15-Nov-2010	From Version 6 to 7	Changed	Smart Array Controller product descriptions were modified and HP BL8x0c i2 32GB (2x16) PC3-10600R-9 Kit was added to Memory.
08-Oct-2010	From Version 5 to 6	Changed	Mot Plug SAS Maximum Internal Storage was increased to 1.2TB, 8Gb Fibre Channel Host Bus Adapter product descriptions were revised in Fibre Channel Support, Smart Array Controller Support was updated, HP 450GB and 600GB 6G SAS 10K rpm SFF Dual Port Enterprise Hard Drives were added to Hard Drives and ProLiant BL c-Class Enclosure and Server Blade Hardware Installation and Delivers onsite hardware installation, system configuration and startup of server platforms and components were removed from HP Care Pack Series.
20-Aug-2010	From Version 4 to 5	Changed	Note was added to HP Onboard Administrator in Glossary of Integrity Server Blades Management Software Product Description and HP BladeSystem c3000 tower enclosure was removed from At A Glance Enclosure.
09-Aug-2010	From Version 3 to 4	Changed	Revised the images to reflect the correct callout line style.
19-Jul-2010	From Version 2 to 3	Changed	Maximum memory was increased to 192 GB
			Power Specifications note was completely revised What's New was added to the Overview

Summary of Changes

			OpenVMS 8.4 and Microsoft Windows Server 2008 for Itanium-based systems were added to OS Systems
			HP BL8x0c i2 16GB Memory was added
07-May-2010	From Version 1 to 2	Changed	Changes made within the Standard Features, Models and
			Technical Specifications sections.

© Copyright 2015 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Microsoft and Windows NT are US registered trademarks of Microsoft Corporation. Intel, the Intel logo, Xeon and Xeon Inside are trademarks of Intel Corporation in the U.S. and other countries.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less.

